



SPECIFICATIONS SHEET

MOBILE CONCRETE BOOM PUMPS



MODEL	UNFOLDING HEIGHT	OUTRIGGER FRONT	OUTRIGGER REAR	TRUCK LENGTH	ONE SIDE SUPPORT FRONT	ONE SIDE SUPPORT REAR
20M	4.2	3.6	2.6	8.5	3.1	2.5
28M	5.9	5.6	2.5	10.0	4.1	2.5
34M	7.9	6.3	3.9	11.0	4.4	3.2
38M	7.3	6.0	7.8	11.2	4.3	5.2
42M	8.0	8.0	8.6	11.4	5.2	5.6
47M	9.5	8.0	9.0	13.1	5.1	6.8
48M	10.0	8.6	9.0	12.7	5.6	5.8
50M	10.0	10.1	11.3	13.6	6.3	6.9
52M	10.3	9.2	12.2	13.9	5.8	7.3
53M	10.6	10.5	10.2	13.8	6.5	6.4
57M	14.8	9.3	12.5	14.3	5.9	7.5
58M	15.9	10.7	10.4	15.7	6.6	6.5
61M	18.2	8.9	12.5	15.9	7.5	7.5
63M	23.0	11.5	12.8	16.5	7.8	8.7
70M	24.5	13.4	13.8	21.5	9.2	9.2

** All technical data are theoretical values and specification are subject to change without prior notice. Dimensions configuration-dependent.

** All measurements are in metres (m).

** Manufactured by CIFA, JUNJIN, Putzmeister, Schwing & Sermac.