



# PRODUCT DATA SHEET

Skudo Window UV Advance is the result of intense development to deal with the extreme conditions imposed on today's construction elements. Skudo Window UV Advance is the perfect solution for all residential and commercial projects that require temporary window and glass protection from start to finish.

Skudo Window UV Advance is has superior film strength sufficient to withstand cement and paint splatter whilst maintaining its protection of the valuable glass and frames for up to 12 months or 160,000 Langley's (UV Radiation). It is also suitable for Low-E glass.



## Product physical properties:

Product name	Window UV Advance
Product type	Paint-able temporary protection
Product use	Peelable protection for Windows and glass
Appearance	Milky liquid
Basic ingredients	Acrylic co-polymer
Health effects	Please see material safety data sheet. Classified as non-hazardous substance

## Product packaging:

Packaging	20 Lt Pail
Spread rate	4-5 sqm per kg
Pail spread rate	80 - 100 sqm
Pails per pallet	32

## Application technique and general information:

Skudo Window UV Advance is easily applied by brush or roller and just as easy to remove by simply peeling off leaving no residue on the surface. Skudo Window UV Advance can be applied up to 5 sqm per kg and with only one coat. For best results, two coats can be applied. Drying time will vary according to the relative humidity and ambient temperature but approximately 2-4 hours would be classified as normal.

Important	Product is not suitable for application on Acrylic. Always perform spot test prior
Storage	Store buckets out of direct sunlight at ambient temperature and humidity
Disposal	Product can be disposed of in local refuse bins or incinerated.

Contact:  
 Skudo - Rob Maniscalco  
 rob@skudogroup.com www.skudogroup.com  
 +61 417 264 003